

| | | | |
|---------------|-----------|------|-----|
| SPECIFICATION | | PAGE | 1/3 |
| PART NUMBER : | TDN203060 | REV. | A |

SPECIFICATION

PART NO: TDN203060

【Approval Stamp Column 】

Customer :



STODA Technologies(Shantou)LTD
Tel : 0754-89918282
Website: www.stodatech.com
Email: sales@stodatech.com
Address: Huanshi east road, Chen nan street , Chaoyang , Shan tou, Guang dong P.R.C

| | | | |
|---------------|--|------|-----|
| SPECIFICATION | | PAGE | 2/3 |
|---------------|--|------|-----|

| | | | |
|---------------|-----------|------|---|
| PART NUMBER : | TDN203060 | REV. | A |
|---------------|-----------|------|---|

1: PHYSICAL DIMENSION

BEFORE COATING


| | | | | | |
|------------------|------|---|-------|----|-----|
| OUTSIDE DIAMETER | (OD) | : | 20.32 | mm | MAX |
| INSIDE DIAMETER | (ID) | : | 12.70 | mm | MIN |
| HEIGHT | (HT) | : | 6.35 | mm | MAX |

AFTER COATING :

| | | | | | |
|------------------|------|---|-------|----|-----|
| OUTSIDE DIAMETER | (OD) | : | 21.08 | mm | MAX |
| INSIDE DIAMETER | (ID) | : | 12.07 | mm | MIN |
| HEIGHT | (HT) | : | 7.11 | mm | MAX |


2: CORE MAGNETIC PARAMETERS

| | | | |
|--------------------------------|---------------------|-------|-----------------|
| EFFECTIVE MAGNETIC PATH LENGTH | (L _e) : | 5.09 | cm |
| EFFECTIVE CROSS SEPCION AREA | (A _e) : | 0.226 | cm ² |
| EFFECTIVE VOLUME | (V _e) : | 1.15 | cm ³ |




3: DC BIASED INDUCTANCE

| | | | |
|-----------------------------|---|--------|----|
| H _{DC} | : | 100 | Oe |
| PERCENT INITIAL PERM(NOM) | : | 63.68% | |
| PERCENT INITIAL PERM(MIN.) | : | 56.50% | |



| | | | |
|---------------|-----------|------|-----|
| SPECIFICATION | | PAGE | 3/3 |
| PART NUMBER : | TDN203060 | REV. | A |
| 4: CORE LOSS | | | |

B_{pk} : 1000 G
 FREQUENCY : 50 kHz
 CORE LOSS (NOMINAL) : 243 mW/cm³
 CORE LOSS (MAXIMUM) : 260 mW/cm³




5: INDUCTANCE

μ_i (REFERENCE) : 60
 AL VALUE (NOMINAL) : 32 nH/N²
 TEST WINDING : N=90, #28 AWG
 FREQUENCY : 10 kHz
 VOLTAGE ON TH2829A : 0.090 V
 AL TOLERANCE : $\pm 8\%$
 TEST INSTRUMENT : TH2829A

6: COATING/PACKAGE

COATING TYPE : Black Epoxy
 VOLTAGE BREAKDOWN (MIN.) : 1000 Vrms
 LIMIT : 0.1 mA, 5 s
 PACKAGE QUANTITY : 1,800 Pcs/Box

| REVISION HISTORY | | | PREPARED | CHECKED | APPROVED |
|------------------|-------------|----------|---|---------|----------|
| REV. | DESCRIPTION | DATE | | | |
| A | FIRST ISSUE | 2022/4/2 |  | | |
| | | | | | |
| | | | | | |